

Redexim
NORTH AMERICA, INC.



VERTI-DRAIN

7215




Building on the tradition of innovative excellence, the Verti-Drain 7215 incorporates the technology of the second-generation line with new and improved features. The 7215 boasts a working width of 61" (1.56m) and can aerate up to 10" (250mm) maximum, making for greater productivity when fit to a 25 hp tractor.

VERTI-DRAIN 7215

The 7215 offers reinforced front and rear rollers, as well as a lighter frame than the 73 series, thus having lower horsepower requirements.

- Maintenance free, self-lubricated sealed bearings on all pivot points
- Fully sealed greasable bearings on crankshaft, PTO and rollers
- Lifetime grease in gearbox



Verti-Drains adjustable parallelogram design shatters the soil, and also allows for clean coring, on all models.



WORKING SPECIFICATIONS

Working width	61" (1.56 m)
Working depth	Up to 10" (250 mm)
Tractor speed@500 rev's at PTO	
Spacing 2 1/2" (65 mm)	Up to 0.60 mph (1.00 km/h)
Spacing 4" (100mm)	Up to 1.00 mph (1.50 km/h)
Spacing 6 1/2" (165mm)	Up to 1.60 mph (2.50 km/h)
PTO speed: (max)	Up to 500 rpm
Weight	1,210 lbs (550 Kg)
Hole spacing side-to-side	4" (100 mm) @ 3/4" (18 mm) holes 2.5" (65 mm) @ 1/2" (12 mm) holes
Hole spacing in driving direction	1" - 6 1/2" (25 - 165 mm)
Recommended tractor size	25 HP with lift capacity of minimum 1,540 lbs (700 Kg)
Capacity (maximum)	
Spacing 2 1/2" (65 mm)	Up to 16,813 sq ft (1,563 sq m)/ hour
Spacing 4" (100mm)	Up to 25,866 sq ft (2,404 sq m)/ hour
Spacing 6 1/2" (165mm)	Up to 42,678 sq ft (3,966 sq m)/ hour
Shipping dimensions	69" x 32" x 44" (1.7m x 0.8m x 1.1m)
Maximum tine size	Solid 3/4" x 10" (18 x 250 mm) Hollow 1" x 10" (25 x 250 mm)
Three point linkage	3- point CAT 1
Transmission oil	Life time grease EP 00
Lubrication grease	EP 2
Standard items	Set solid tines to 1/2" x 10" (12mm x 250mm) Front and rear roller 3- shuttle gearbox

FEATURES / BENEFITS

FEATURE	BENEFIT
Unique adjustable parallelogram forced heave	Shatters compaction in any ground conditions. Versatile with single-point adjustment for optimum results and hollow coring
3-speed gearbox	Matches your tractor's ground speed exactly to achieve desired hole spacing. Creep speed tractor gear not essential
Sealed bearings not bushings	Long maintenance free life
Higher working speed	Greater working capacity
Useable playing surface	Aerate at any time without interruption of play
1/2" (12 mm) or 3/4" (19 mm) solid & hollow tines	Choice of tines for varying conditions

CALL FOR YOUR FREE DEMO TODAY!

The market leading range of Verti-Drains have outsold and outperformed all competitors for the past twenty years. With a model to suit virtually every application, it's the widest range available anywhere.

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office at 636-326-1009.



Redexim
NORTH AMERICA, INC.
Redexim North America Inc.
29 Cassens Court
Fenton, MO 63026, USA
Tel: 636-326-1009
Fax: 636-326-4884
www.redexim.com
E-mail: redexim@aol.com