













The 7626 is the heaviest and toughest Verti-Drain on the market. It is the ideal machine for the toughest of soil conditions, where a high productivity is needed. It weighs considerably more than the 75-series, and it has a heavier gearbox, PTO and rear roller support. Its adjustments have been made simpler. The tine-depth adjustments are made comfortably from the tractor seat via the hydraulic controls, while the original amount of 'heave' on the tine is left intact.

## VERTI-DRAIN 7826



Verti-Drains adjustable parallelogram design shatters the soil, and also allows for clean The optional wheel support is constructed extra robustly, while it falls within the 104" (2.6 m) working width of the Verti-Drain. The forward speed is faster than that of the 75-series.



3.34		
WORKING SPECIFICATIONS	Working width	104" (2.6 cm)
	Working depth	up to 16" (40 cm) max.
	Tractor speed@500 rev's at PTO Spacing 2'/2" (65 mm) Spacing 5" (130mm) Spacing 7"/2" (195mm)	spacing @ 0.45 mph (0.72 km/h) spacing @ 0.90 mph (1.4 km/h) spacing @ 1.35 mph (2.17 km/h)
	PTO speed: (max)	up to 500 rpm
	Weight	4,254 lbs. (1,930 kg)
	Hole spacing side-to-side	2 <sup>1</sup> / <sub>2</sub> " (663 mm) with <sup>1</sup> / <sub>2</sub> " (12 mm) tines 5" (127 mm) with 1" (25 mm) tines
	Recommended tractor size	7626 – 65 hp, lift cap. 5,070 lbs (2,299 kg) 7626H – 55 hp - double acting hydraulic connection is required
	Capacity (maximum) Spacing 2'/2" (65mm) Spacing 5" (130mm) Spacing 7"/2" (195mm)	20,989 sq ft/hr (1,950 sq m/hr) 41,979 sq ft/hr (3,900 sq m/hr) 62,969 sq ft/hr (5,850 sq m/hr)
	Standard Tines	3/4" x 16" (19 mm x 406mm) solid
	Three point linkage	Cat 2
	Accessories available	Hydraulic Wheel Kit 1/2" (12 mm) & 3/4" (19mm) turf hold down kits
-		

S	「「「「「「「「」」」、「「」」、「」」、「「」」、「」」、「」」、「」」、「	2671年1月1日的建筑和4、47月1月1日(三日和
FEATURES / BENEFITS	FEATURE	BENEFIT
	hydraulic depth adjustment	no need to leave the tractor seat
	104" (2.6 m) working width	high productivity
	weighs 4,254 lbs. (1,930 kg)	able to penetrate even in the roughest conditions
	heavier gear box, rear roller and PTO	able to withstand the most punishing conditions
	optional bogey wheel kit	transfers the weight of the machine off of the tractor

## CALL FOR YOUR FREE DEMO TODAY!

The market leading range of Verti-Drains have outsold and outperformed all competitors for the past twenty years. With a model to suit virtually every application, it's the widest range available anywhere.

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office at 636-326-1009.

## Redexim

Redexim North America Inc. 29 Cassens Court Fenton,MO 63026,USA Tel: 636-326-1009 Fax: 636-326-4884 www.redexim.com E-mail: redexim@aol.com