

Redexim
NORTH AMERICA, INC.



LEVEL-SPIKE

1700/2200



The Level-Spike is built tough and can be operated at speeds of 8.7mph (14 kmh) or more. The choice of available widths enables the customer to match the machine to their tractor and their specific requirements. There is an exceptionally wide range of knife options. There is an optional hydraulic weight transfer system which utilizes the tractor's hydraulics to force the tines into the ground providing maximum aeration and drainage.

LEVEL-SPIKE 1700/2200



Deep penetration - Improves drainage and opens up the turf in both winter and summer programs

Fast operation - Covers large areas rapidly leaving a quality finish

5 optional types of knives - truckster, deep slitting, twist, fine slitting, coring spoon

Rear rollers - Optional rear rollers available

Weight options - hydraulic or static weights. Enables the user to obtain the most from his tractor and achieve maximum penetration



WORKING SPECIFICATIONS

Model	Level-Spike 1700	Level-Spike 2200
Length	55" (1.4m)	55" (1.4m)
Road width	73" (1.9m)	97" (2.5m)
Working width	71" (1.8m)	94" (2.4m)
Working depth	up to 10" (0.25m)	up to 10" (0.25m)
Height	39" (1.0m)	39" (1.0m)
Weight	891lbs (405kg)	1,091lbs (495kg)
Hole spacing side to side		
With standard knives	6" (150 mm)	6" (150 mm)
With fine slit knives	3" (75 mm)	3" (75 mm)
Hole spacing in drive direction		
With 3 knives per disk	17" (440 mm)	17" (440 mm)
With 4 knives per disk	13" (330 mm)	13" (330 mm)
With 6 knives per disk	8½" (220 mm)	8½" (220 mm)
With 12 knives per disk	4½" (110 mm)	4½" (110 mm)

FEATURES / BENEFITS

FEATURE	BENEFIT
Deep penetration	Improves drainage
Close slitting	Better drainage, less thatch, reduces irrigation
Fast operation	Up to 8.7 mph (14kmh), finish early
Choice of 2 sizes	Match machine to job and tractor
Weight transfer options	Hydraulic system or static weights guarantee full penetration

CALL FOR YOUR FREE DEMO TODAY!

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office at 636-326-1009.



Redexim
NORTH AMERICA, INC.
Redexim North America Inc.
29 Cassens Court
Fenton, MO 63026, USA
Tel: 636-326-1009
Fax: 636-326-4884
www.redexim.com
E-mail: redexim@aol.com