



# RINK TOP DRESSER

DS800



The Rink DS 800 is a topdresser with dual spinners with a spread pattern variable up to 10 m. The operation of the belt and spinners can be done from the tractor seat, by switching the hydraulic lever. No unnecessary drop of material takes place between stopping and operation, since the material release gate automatically closes when the belt is stopped. The spinner disks have been designed in a way that they will handle wet material very well.

# RINK TOP DRESSER DS 800

The Topdresser DS800 is used for spreading small-grained, loose material, such as sand, small granular material or similar products. The spreading equipment of the Topdresser is driven by a gear box with hydraulic motor for conveyor belt and a separate hydraulic motor for each spinner. The number of revolutions of the hydraulic system for the conveyor belt and spinners can be continuously adjusted independently by means of a flow divider. Spreading density or spreading amount can be determined by the tractors speed, spinner speed and conveyor belt speed.



## WORKING SPECIFICATIONS

|                                       |                           |
|---------------------------------------|---------------------------|
| Length                                | 95" (2.40 m)              |
| Width                                 | 57" (1.45 m)              |
| Height                                | 40" (1.05 m)              |
| Loading Capacity                      | 1.04 cu yd (0.80 cu m)    |
| Total weight capacity                 | 3,300 lbs (1,500 Kg)      |
| Empty weight                          | 710 lbs (approx. 320 kg)  |
| Spreading width                       | up to 36' (12 m)          |
| Tire equipment                        | mounted version(no tires) |
| Speed Limit                           | 19 mph (30 km/h)          |
| Towing capacity                       | Min 1,200 Kg (30 HP)      |
| Spreading amount                      | (2,600 lbs) lift capacity |
| Hydraulic connected load              | continuously adjustable   |
| Min conveying capacity towing vehicle | 6 gal/min (25 l/min)      |
| Minimum pressure towing vehicle       | 1,960 PSI (140 bar)       |

## FEATURES / BENEFITS

| FEATURE                         | BENEFIT                                                              |
|---------------------------------|----------------------------------------------------------------------|
| dual spinners                   | variable spread pattern                                              |
| hydraulic controls              | the belt and spinners can be controlled w/o leaving the tractor seat |
| automatically closing feed gate | no waste of material                                                 |
| new spinner design              | will work with even wet material                                     |

## CALL FOR YOUR FREE DEMO TODAY!

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office at 636-326-1009.



**Redexim North America Inc.**  
 29 Cassens Court  
 Fenton, MO 63026, USA  
 Tel: 636-326-1009  
 Fax: 636-326-4884  
 www.redexim.com  
 E-mail: redexim@aol.com